



TRUCK, BUS & HEAVY EQUIPMENT BATTERIES

TRAIN

G I

RUAD



BATTERIES BUILT TOUGH FOR COMMERCIAL CONDITIONS

CENTURY TRUCK, BUS AND HEAVY EQUIPMENT BATTERIES REPRESENT THE LATEST IN PERFORMANCE AND RELIABILITY FOR HAULAGE AND LIGHT COMMERCIAL VEHICLES.

Designed and built in Australia[^] to better suit our harsh environment and extreme climate, they deliver what drivers and fleet managers really want longer life with less down time.

Delivering more than just superior starting power, Century Truck, Bus and Heavy Equipment batteries can sustain constant current loads over extended periods to run on-board accessories for longer.



CENTURY BATTERIES IS AUSTRALIA'S OLDEST AND MOST RECOGNISED BATTERY MANUFACTURER WITH A PROUD HISTORY OF DESIGNING AND MANUFACTURING BATTERIES IN AUSTRALIA SINCE 1928.

Our reputation for quality and innovation has been refined and demonstrated over many decades. In this time we have developed the manufacturing expertise and technical know-how to develop a range of batteries better suited to Australia's extreme climate and harsh conditions.

Today we pride ourselves in offering our customers a range of market leading products and services which continue to set new standards in technology and performance.

^Selected items only.

	CHOOS	ING THE	RIG
	TRUCK BUS	Century HITRA HI PERFORMANCE AUSTRALIA	Ki PERFO
	Battery Type	Ultra Hi Performance Severe Service N70ZZHX	Hi Pe N70
	Fitment	Long haul on-highway interstate trucks	Short hai instras
	Application	Starting and semi cycling for on-board accessories*	S
	Performance	730 CCA 180 RC 95 AH	78 16
	Vibration Resistance	$\checkmark \checkmark \checkmark$	
d	SPECIFICATIONS		
	Design	LOW MAINTENANCE DESIGN	Ø
	Special Features	 » Platelock[™] technology » Full frame cast plate design » Glass mat separator » Labyrinth lid technology 	» Platelock ^T » Full frame » PE separa » Labyrinth
12	Warranty	18 MONTH WARRANTY	12





Are you short on time?

Use Century's online battery finder to quickly and easily find the most suitable battery for your needs.

† Terms and conditions apply. Refer to individual warranty statement attached to each battery. *Low current draw accessories (shallow cycling).

HT BATTERY

ZZH

MADE IN A AUSTRALIA	ULTRA ULTRA HI FERFORMANCE MUSTRALIA	Rentury IN PERFORMANCE MADE IN AUSTRALIA
ance MF	• Ultra Hi Performance NS70X MF	• Hi Performance NS70 MF
highway trucks	Short haul off-highway vehicles with extra starting power	Short haul off-highway vehicles
g	Starting	Starting
	720 CCA 160 RC	650 CCA 140 RC
	$\checkmark \checkmark$	\checkmark
TENANCE DESIGN	MAINTENANCE FREE DESIGN	MAINTENANCE FREE DESIGN
nology Iate design hnology	 » Cast positive plates » Expanded negative plates » PE separators » Labyrinth lid technology 	 » Expanded positive plates » Expanded negative plates » PE separators » Labyrinth lid technology
NTH RANTY	24 MONTH WARRANTY	24 MONTH

ONLINE BATTERY FINDER

1 Visit www.centurybatteries.com.au 2 Key in the vehicle make, model and year 3 The online Battery Finder quickly finds the most suitable battery for your needs

THE CENTURY BATTERIES DIFFERENCE

CENTURY'S NEW RANGE OF BATTERIES CONTINUE TO BUILD ON CENTURY'S REPUTATION FOR QUALITY AND INNOVATION.

Century Ultra Hi Performance Severe Service batteries are the latest in performance and reliability for trucks, farm and heavy equipment. Incorporating industry leading technology and engineering innovation, these batteries are built to withstand the challenges of Australia's extreme climate, and harsh conditions.

6 CARRY HANDLE

Ergonomic design provides a thicker grooved carry handle for comfort.

7 STATE OF CHARGE INDICATOR

For on the spot diagnosis of battery condition.

(8) CAST ON STRAP

Thicker cast on strap ensures durability and lower electrical resistance for longer battery life.

LABYRINTH LID TECHNOLOGY

Advanced double lid to assist in reducing water loss and promote longer battery life.

DEATELOCK[™] TECHNOLOGY

Combats vibration and damage from rough uneven roads.

enture ULTRA HI PERFORMANCE

9=== / ()== / ()=

- » Superior performance
- » Improved strength and durability in commercial conditions
- » Enhanced endurance and vibration resistance
- » Designed to combat damage from rough uneven roads^






ITEM ID	BATTERY TYPE	WARRANTY (MONTHS) [†]	CCA -18°C	RC @ 25°C	AH @ 20HR		TH C measurements in mm)		••	KG				
						L	W	Н	TH	POLARITY	WEIGHT	TERM. TYPE	HOLD DOWN	SPECIAL FEATURES
ULTRA HI PERFORMANCE TRUCK														
122112	N70ZZHX	18	730	180	95	305	171	202	225	D	23.9	STD	SIDE*	CH, CI, GM, LM, MIA, MR, PL, VR
122113	N70ZZLHX	18	730	180	95	305	171	202	225	С	23.9	STD	SIDE*	CH, CI, GM, LM, MIA, MR, PL, VR
127102	NS70X MF	24	720	160	85	259	171	202	225	D	19.5	STD	SIDE	CH, CI, CV, FA, MR, MF, MIA
127103	NS70LX MF	24	720	160	85	259	171	202	225	С	19.5	STD	SIDE	CH, CI, CV, FA, MR, MF, MIA

[†]Conditions apply. Refer to individual warranty statements attached to each battery. [^]Selected items only. *Side ledge hold down available on locally made products from October 2016

CELL LAYOUT



SPECIAL FEATURES GLOSSARY

СН	Carry Handles	GM	Glass Mat Separator	MR	Mud Rack
CI	State of Charge Indicator	LM	Low Maintenance	PL	Platelock Technology
C۷	Central Venting	MIA	Made in Australia	VR	Vibration Resistant
FA	Flame Arrestor	MF	Maintenance Free		

1 CAST PLATE

3

Thicker, full frame cast plate provides increased strength and lower internal resistance, promoting superior starting power, improved vibration resistance and longer service life.

2) ENHANCED PLATE PASTE

Enhanced paste formulation reduces water loss and improves charge acceptance for superior performance and longer life.

3 GLASS MAT SEPARATORS

The Glass Mat Separator constrains the paste into the plate improving durability and increasing vibration resistance.

(4) MUD RACK

Improves plate support for greater vibration resistance and helps prevent short circuits.

5 POLYPROPYLENE CASE

Reinforced design provides durability to withstand shock and vibration.

Ultra Hi Performance

The clear choice for professional drivers, providing exceptional performance and longer life in heavy haulage applications.





Standard **Terminal Post** (STD)

Threaded Terminal Post (TH)



Hi Performance

Designed and built tough in Australia to provide dependable performance and reliability in short haul off-highway applications.

- » Lower self-discharge and reduced water loss
- » Improved strength and durability in commercial conditions
- » Designed to combat vibration and damage from rough uneven roads



E	BA	MAR MO	Û U	RC	АН	(all measurements in mm)			Po					
						L	W	Н	TH		WEIGHT	TERM. TYPE	HOLD DOWN	SPECIAL FEATURES
HI PERFORMANCE TRUCK														
123102	N70ZZH MF	12	780	160	90	305	171	202	225	D	23.9	STD	SIDE*	CH, CI, CV, FA, MF, MR, MIA, PL, VR
123103	N70ZZLH MF	12	780	160	90	305	171	202	225	С	23.9	STD	SIDE*	CH, CI, CV, FA, MF, MR, MIA, PL, VR
123104	NS70 MF	24	650	140	75	259	171	202	225	D	18.7	STD	SIDE	CH, CI, CV, FA, MF, MIA, MR
123105	NS70L MF	24	650	140	75	259	171	202	225	С	18.7	STD	SIDE	CH, CI, CV, FA, MF, MIA, MR

E Century

HI PERFORMANCE

0=10=10=10-

12

*Side ledge hold down available on locally made products from October 2016. An selected items only. †Conditions apply. Refer to individual warranty statements attached to each battery.



12 Mon Warrat	2	AVY DU	FOR EQU	HEAVY			PLATE TECHN VIBRA	<section-header><section-header><section-header><text><text><list-item><list-item><list-item></list-item></list-item></list-item></text></text></section-header></section-header></section-header>						
ITEM ID	BATTERY TYPE	WARRANTY (MONTHS) ⁺	CCA -18°C	RC @ 25°C	AH @ 20HR	¢ H ↓ (all n	neasuren	$ \begin{array}{c} \uparrow \\ \uparrow \\ \uparrow \\ \downarrow \\ \downarrow \\ \neg \\ \neg \\ H \end{array} $	nm) TH	POLARITY		TERM. TYPE	HOLD DOWN	SPECIAL FEATURES
HEAV	Y DUTY													
121106	26¥	12	800	280	143	305	175	200	220	А	21	STD	-	CH, LM, VR
105117	84 MF	12	560	95	50	200	172	183	202	D	13.3	STD	-	CH, CI, CV, FA, MF, MR, PL, VR
120100	86	12	670	160	86	348	170	210	238	С	25.1	STD	-	CH, LM, MIA, MR, PL, VR
125100	86 MF	12	830	180	100	330	170	217	238	Н	25.5	STD	-	CH, CI, CV, FA, MF, MR, PL, VR
120102	86Z	12	720	180	92	348	170	210	238	С	25.6	STD	-	CH, LM, MIA, MR, PL, VR
125101	86Z MF	12	950	180	95	330	170	217	238	Н	24	STD	-	CH, CI, CV, FA, MF, MR, PL, VR
125102	86ZT MF	12	950	180	95	330	170	217	238	Н	24	TH	-	CH, CI, CV, FA, MF, MR, PL, VR
121121	89	12	680	210	118	345	175	262	235	С	31.3	STD	-	CH, MR, VR, LM
121111	94 Squat	12	890	255	135	506	206	180	203	Е	25.1	STD	-	CH, CV, FA, GM, LM, MR, PL, VR
125103	N100 MF	12	740	182	100	405	175	210	235	D	25.1	STD	-	CH, CI, CV, FA, GM, MF, MR, PL, VR
125115	N100L MF	12	740	182	100	405	175	210	235	С	25.1	STD	-	CH, CI, CV, FA, GM, MF, MR, PL, VR
125104	N120 MF	12	900	230	135	505	180	210	240	F	32.1	STD	-	CH, CI, CV, FA, MF, MR, PL, VR
121107	N120	12	740	230	120	500	175	210	235	F	34.9	STD	-	CH, GM, LM
125105	N150 MF	12	1000	300	155	500	220	210	235	F	38.4	STD	-	CH, CI, CV, FA, MF, MR, PL, VR
121108	N150	12	885	280	150	500	220	210	235	F	43.9	STD	-	CH, GM, LM
125116	N150L MF	12	1000	300	155	500	220	210	235	E	38.4	STD	-	CH, CI, CV, FA, MF, MR, PL, VR
121126	N165	12	955	370	180	512	221	194	220	Е	45.9	STD	-	CH, GM, LM
125106	N200 MF	12	1200	430	200	520	275	220	240	F	51.5	STD	-	CH, CI, CV, FA, MF, MR, PL, VR
121109	N200	12	1100	400	185	515	275	215	240	F	53.4	STD	-	CH, GM, LM
121123	N200LS	12	1150	505	225	518	276	216	242	E	59.9	STD	-	CH, GM, LM
121112	4D-N150Z	12	950	300	90	528	214	224	246	F	43.9	STD	-	CH, GM, LM, MR, PL, VR
121113	8D-N200Z	12	1300	430	200	528	277	224	246	F	57.9	STD	-	CH, GM, LM, MR, PL, VR
125111	8DMF1200	12	1200	430	200	500	270	215	245	F	50.7	STD	-	CH, CI, CV, FA, GM, MF, MR, PL, VR
6 volt bat	tery [†] Conditions	s apply. F	Refer to i	ndividua	al warra	nty state	ements a	attached	l to each	batte	ry. ^In sele	cted items or	nly.	



For more information on Century's range of products and services, visit www.centurybatteries.com.au







Find us on Facebook 🏹 Follow us on Twitter

For more information contact: